

Wire Rope Fittings

Stock No.	Rope Size	Inside Length of U-Bolt	Min. No. of Clips for Max. Strength	Approx. Wt. Per 100 Pcs.
20900	1/16*	23/32	2-4	3.0
20905	1/8*	29/32	2-4	4.5
20910	3/16	15/16	2-4	6.5
20915	1/4	1 1/32	2-4	12.0
20920	5/16	1 5/16	2-4	12.0
20925	3/8	1 1/2	2-4	19.0
20930	7/16	1 7/8	3-4	21.8
20935	1/2	1 7/8	3-4	37.0
20940	9/16	2 1/4	3-4	46.0
20945	5/8	2 3/8	3-4	54.0
20950	3/4	2 3/4	4-5	80.0
20955	7/8	3 1/8	4-5	116.0
20960	1	3 1/2	4-5	137.0
20965	1-1/8	3 7/8	6-8	267.0
20970	1-1/4	4 1/4	6-8	328.0


NOTE: These products are manufactured to Edward W. Daniel Co. quality standards via global contracts.

USE CLIPS PROPERLY FOR MAXIMUM EFFICIENCY

1. U-bolt should bear on dead end of rope.
2. Use recommended number of clips, depending on safety requirement.
3. Spacing between clips should be 6 times the rope diameter.
4. Nuts should be retightened after initial load.

Stock No.	Rope Size	Threads Per In.	Recommended Torque To Assemble	Approx. Wt. Per 100 Pcs.
18651	1/8	20	35 ft. lb.	7.0
18653	3/16	20	80	16.0
18654	1/4	16	145	25.0
18655	5/16	16	225	50.0
18656	3/8	16	325	75.0
18658***	1/2	12	575	200.0
18662***	3/4	10	1300	500.0

***These products will be discontinued when stock is depleted.



Provides an efficiency of over 90% of rated wire-rope strength - Accommodates 6x19 (I.W.R.C.) or 7x19 right-regular-lay wire rope - Easy-to-use 3 piece assembly - can be field assembled faster than U-bolt clips, yet offers nearly same smooth configuration as a swaged fitting - Encloses potentially hazardous wire ends - Meets or exceeds all requirements for military standard MS-16843; and conforms to Federal Specification FF-C-450.

Stock No.	Size Rope Dia.	Dimensions						Max. Pin Dia. P	Approx. Wt. Per 100 Pcs.
		B	C	F	L	W			
40300	1/4	1 1/16	7/8	7/16	2 1/4	1 3/16	1 1/2	9.0	
40305	5/16	2	1 1/16	1 7/32	2 5/8	1	1 7/8	13.5	
40310	3/8	2 1/8	1 1/8	2 1/32	2 3/4	1 1/16	2	26.0	
40315***	7/16	2 1/4	1 1/4	3/4	3 1/16	1 3/16	2 1/4	31.0	
40320	1/2	2 3/4	1 1/2	7/8	3 3/4	1 7/16	2 7/8	43.0	
40325***	9/16	2 3/4	1 1/2	1 5/16	3 3/4	1 7/16	2 5/8	48.0	
40330***	5/8	3 1/4	1 3/4	1 1/32	4 3/16	1 5/8	3	76.0	
40335***	3/4	3 3/4	2	1 1/4	5	1 7/8	3 3/4	142.5	
40340***	7/8	4 1/4	2 1/4	1 7/16	5 1/16	2 1/8	4 1/8	189.0	
40345***	1	4 5/8	2 1/16	1 5/8	6 7/16	2 1/2	4 15/16	280.0	
40350***	1-1/8 - 1-1/4	5 1/4	2 15/16	1 7/8	7 1/4	2 3/4	5 7/16	402.0	

A heavy thimble with deep score, made from heavy gauge steel. Designed to withstand the crushing strains imposed by severe loads. Hot-dip galvanized in accordance with ASTM Specification A 153 for maximum corrosion protection. All sizes meet or exceed Federal Specification FF-T-276b for Type III thimbles.

NOTE: These products are manufactured to Edward W. Daniel Co. quality standards via global contracts.

***These products will be discontinued when stock is depleted.

Malleable Wire Rope Clips

- 1030 Carbon Steel
- Zinc Plated



- All regular hex nuts.
- Clips meet Federal Specification FF-C-450, Type I, Class 2
- Bulk pack

Safe-Line Clamps

- Plated
- Carbon Steel Construction



Can be used for load carrying applications.

Heavy Wire Rope Thimbles

- 1030 Carbon Steel
- Hot Galvanized

